



Industrial / Small Farm / Passenger

Bladder Code	Reference Size (mm)	Crown Gauge A (mm)	Foot I.D. B (mm)	Foot Height C (mm)	Foot Width D (mm)	Neck Gauge E (mm)	Outside Diameter F (mm)	Overall Height G (mm)	Effective Perimeter H (mm)	Wt. Lbs (Kilos)	Etch Page 19
7374	4" (mm)	0.30 / 7.6	2.50 / 63.5	0.50 / 12.7	0.18 (2) / 4.6	0.28 / 7.1	5.00 / 127.0	7.94 / 201.7	8.44 / 214.4	1.25 / 0.57	4
7375	5" (mm)	0.30 / 7.6	2.50 / 63.5	0.50 / 12.7	0.18 (2) / 4.6	0.28 / 7.1	5.00 / 127.0	8.94 / 227.1	9.44 / 239.8	1.50 / 0.68	4
4789	6" small (mm)	0.30 / 7.6	3.75 / 95.3	0.58 / 14.7	0.31 / 7.9	0.26 / 6.6	6.54 / 166.1	8.44 / 214.4	9.12 / 231.6	1.90 / 0.86	5
4171	8" small (mm)	0.33 / 8.4	4.63 / 117.6	0.66 / 16.8	0.44 / 11.2	0.31 / 7.9	8.50 / 215.9	10.25 / 260.4	11.18 / 284.0	3.00 / 1.36	1
4173	8" medium (mm)	0.33 / 8.4	4.63 / 117.6	0.66 / 16.8	0.44 / 11.2	0.31 / 7.9	8.50 / 215.9	13.10 / 332.7	14.00 / 355.6	4.20 / 1.90	1
8188	8" large (mm)	0.37 / 9.4	4.63 / 117.6	0.66 / 16.8	0.44 / 11.2	0.31 / 7.9	8.50 / 215.9	17.48 / 444.0	18.38 / 466.9	5.70 / 2.59	1
8189	8" X-large (mm)	0.37 / 9.4	4.63 / 117.6	0.66 / 16.8	0.44 / 11.2	0.31 / 7.9	8.50 / 215.9	19.48 / 494.8	20.38 / 517.7	6.40 / 2.90	1
5339	9"/10" (mm)	.33/.28 / 8.4	5.50 / 139.7	0.88 / 22.4	0.50 / 12.7	0.38 / 9.7	9.50 / 241.3	15.00 / 381.0	15.72 / 399.3	5.90 / 2.68	1
7370	10" (mm)	0.30 / 7.6	6.25 / 158.8	0.82 / 20.8	0.46 / 11.7	0.38 / 9.7	11.50 / 292.1	15.71 / 399.0	16.50 / 419.1	7.20 / 3.27	1
2196	10" (1) (mm)	0.48 / 12.2	6.92 / 175.8	0.84 / 21.3	0.50 / 12.7	0.41 / 10.4	11.38 / 289.1	18.38 / 466.9	18.9 / 480.1	10.80 / 4.90	11
4776	12" (mm)	0.39 / 9.9	8.00 / 203.2	0.82 / 20.8	0.50 / 12.7	0.38 / 9.7	11.88 / 301.8	12.25 / 311.2	13.40 / 340.4	8.00 / 3.63	1
6299	13"-15" X-small (mm)	0.33 / 8.4	8.60 / 218.4	0.82 / 20.8	0.50 / 12.7	0.38 / 9.7	12.98 / 329.7	13.28 / 337.3	14.12 / 358.6	7.70 / 3.49	1
6228	13"-15" X-small (mm)	0.33 / 8.4	8.60 / 218.4	0.82 / 20.8	0.50 / 12.7	0.38 / 9.7	15.20 / 386.1	13.64 / 346.5	16.14 / 410.0	9.80 / 4.44	1
7632	13"-15" X-large (mm)	0.33 / 8.4	8.60 / 218.4	0.82 / 20.8	0.50 / 12.7	0.38 / 9.7	15.20 / 386.1	16.06 / 407.9	18.64 / 473.5	10.90 / 4.95	1

(1) "L" Type Foot Configuration
 (2) 30° Tapered Toe Angle